



SAFETY DATA SHEET

TOP FLIGHT

Infosafe No.: LQ66R
Issued Date: 13/05/2016
Issued by: JASOL AUSTRALIA

CLASSIFIED AS HAZARDOUS

1. IDENTIFICATION

GHS Product Identifier

TOP FLIGHT

Product Code

2001470

Company Name

JASOL AUSTRALIA

Address

Level 3, 187 Todd Road PORT MELBOURNE
VIC 3207 Australia

Telephone/Fax Number

Tel: 1800 334 679

Fax: 03 95809902

Emergency phone number

1800 629 953

Recommended use of the chemical and restrictions on use

Heavy Duty low foam chlorinated dishwashing detergent for automatic dispenser. Refer to product label for instructions. Non-domestic use only.

Other Information

Jasol (a division of George Weston Foods Limited) believes the information in this document to be accurate as at the date of preparation noted in the header of the SDS, but to the maximum extent permitted by law, Jasol accepts no responsibility for any loss or damage caused by any person acting or refraining from action because of this information.

The provision of this information should not be construed by anyone as a recommendation to use this product. In particular, no one should use any product in violation of any patent or other intellectual proprietary rights or in breach of any statute or regulation.

Users should rely on their own knowledge and inquiries and make their own determination as to the applicability of this information in relation to their particular purposes and specific circumstances. Each user should read this SDS and consider the information in the context of how the product will be handled and used in the workplace and in conjunction with other substances or products.

2. HAZARD IDENTIFICATION

GHS classification of the substance/mixture

Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia

Classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)

Eye Damage/Irritation: Category 1

Skin Corrosion/Irritation: Category 1

STOT Single Exposure: Category 3 (respiratory tract irritation)

Signal Word (s)

DANGER

Hazard Statement (s)

H314 Causes severe skin burns and eye damage.

H335 May cause respiratory irritation.

Pictogram (s)

Corrosion, Exclamation mark, Environment



Precautionary statement – Prevention

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P264 Wash contaminated skin thoroughly after handling

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statement – Response

P301+P330+P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER or doctor/physician.

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

P363 Wash contaminated clothing before reuse.

Precautionary statement – Storage

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Precautionary statement – Disposal

P501 Dispose of contents/container to an approved waste disposal plant

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients

Name	CAS	Proportion
Sodium carbonate	497-19-8	10-30 %
Sodium hydroxide	1310-73-2	10-30 %
Sodium Metasilicate	10213-79-3	0-10 %
Sodium Dichloroisocyanurate dihydrate	51580-86-0	0-10 %
Ingredients determined not to be hazardous		Balance

4. FIRST-AID MEASURES

Inhalation

If inhaled, remove affected person from contaminated area and keep at rest in a position comfortable for breathing. Seek medical attention. Apply artificial respiration if NOT breathing and immediately seek medical attention.

Ingestion

Do NOT induce vomiting. Wash/rinse out mouth thoroughly with water. Seek immediate medical attention.

Skin

If on skin (or hair) remove/take off all contaminated clothing immediately after handling. Seek immediate medical attention and wash/rinse skin gently and thoroughly with water/shower and non-abrasive soap for 15 minutes. Ensure contaminated clothing is washed before re-use or discard.

Eye contact

If in eyes, hold eyelids apart and flush the eyes continuously with running water. Remove contact lenses, if present and easy to do. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. Seek immediate medical attention.

First Aid Facilities

Eyewash, safety shower and normal washroom facilities.

Advice to Doctor

Product contains a high proportion of sodium hydroxide and a low proportion of SDIC and soda ash. Vomiting has not been induced because of risk of aspiration into the lungs. If swallowed, may cause holes in stomach and intestines. Evacuation of stomach should not be attempted. Contact Poisons Information Centre.

Most important symptoms/effects, acute and delayed

No adverse health effects expected if the product is handled in accordance with this MSDS and the product label.

Other Information

For advice in an emergency, contact a Poisons Information Centre (Phone Australia 131 126) or a doctor at once.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Carbon dioxide, dry chemical, foam, water fog or water mist.

Unsuitable Extinguishing Media

Do not use water jet.

Hazards from Combustion Products

Under fire conditions this product may emit toxic and/or irritating fumes and gases including carbon dioxide, water vapour, sodium carbonate, chlorine, sodium hypochlorite, cyanuric acid.

Specific Hazards Arising From The Chemical

This product is non combustible.

Contact with aluminium, tin, zinc or galvanised iron may generate hydrogen, a flammable gas. Will react vigorously or violently with acids, generating much heat, and giving off carbon dioxide, a simple asphyxiant and chlorine gas, a toxic gas. Contact with ammonium compounds will generate ammonia, a poisonous gas.

Hazchem Code

2X

Decomposition Temperature

Not available

Precautions in connection with Fire

Fire fighters should wear full protective clothing and self-contained breathing apparatus (SCBA) operated in positive pressure mode. Fight fire from safe location.

6. ACCIDENTAL RELEASE MEASURES

Emergency Procedures

Evacuate all unprotected personnel. Do not allow contact with skin and eyes. Do not breathe dust. It is essential to wear self-contained breathing apparatus (S.C.B.A) and full personal protective equipment and clothing to prevent exposure. Avoid exposure to spillage by sweeping up material avoiding dust generation or dampen spilled material with water to avoid airborne dust, then transfer material to suitable containers. Use absorbent paper dampened with water to pick up remaining material. Wash surfaces well with soap and water. Seal all wastes in labelled containers for subsequent recycling or disposal. Dispose of waste according to applicable local and national regulations. If contamination of sewers or waterways occurs inform the local water and waste management authorities in accordance with local regulations.

7. HANDLING AND STORAGE

Precautions for Safe Handling

Corrosive solids. Attacks skin and eyes. Causes burns. Avoid breathing in dust. Wear suitable protective clothing, gloves and eye/face protection when mixing and using. Use in designated areas with adequate ventilation. Keep containers tightly closed. Ensure a high level of personal hygiene is maintained when using this product, that is, always wash hands after handling, and before eating, drinking, smoking or using the toilet facilities.

Conditions for safe storage, including any incompatibilities

Corrosive. Store in a cool dry well-ventilated area. Store away from oxidising agents and bases/acids. Keep containers closed when not in use, securely sealed and protected against physical damage. Inspect regularly for deficiencies such as damage or leaks. Store in original packages as approved by manufacturer. Ensure that storage conditions comply with applicable local and national regulations. Keep away from acids, aluminium, tin, zinc and galvanised iron.

For information on the design of the storeroom, reference should be made to Australian Standard AS 3780 The storage and handling of corrosive substances.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational exposure limit values

No exposure standards have been established for this material. However, the available exposure limits for ingredients are listed below:

Sodium hydroxide

TWA: 2 mg/m³

TWA (Time Weighted Average): The average airborne concentration of a particular substance when calculated over a normal eight-hour working day, for a five-day week.

Peak Limitation: A ceiling concentration which should not be exceeded over a measurement period which should be as short as possible but not exceeding 15 minutes.

Biological Limit Values

No biological limits allocated.

Appropriate Engineering Controls

This substance is hazardous and should be used with a local exhaust ventilation system, drawing solid/dust away from workers' breathing zone. If the engineering controls are not sufficient to maintain concentrations of particulates below the exposure standards, suitable respiratory protection must be worn. Do not use aluminium, tin, copper or copper alloys, zinc or galvanised iron as materials of construction.

Respiratory Protection

If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable dust/particulate filter should be used. Refer to relevant regulations for further information concerning respiratory protective requirements.

Reference should be made to Australian Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.

Eye Protection

Safety glasses with full face shield should be used. Eye protection devices should conform to relevant regulations.

Eye protection should conform with Australian/New Zealand Standard AS/NZS 1337 - Eye Protectors for Industrial Applications.

Hand Protection

Wear gloves of impervious material such as rubber or plastic. Final choice of appropriate gloves will vary according to individual circumstances. i.e. methods of handling or according to risk assessments undertaken. Occupational protective gloves should conform to relevant regulations.

Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.

Body Protection

Suitable protective workwear, e.g. cotton overalls buttoned at neck and wrist is recommended. Chemical resistant apron is recommended where large quantities are handled.

Other Information

No exposure standards have been established for this material, however, the TWA exposure standards for dust not otherwise specified is 10 mg/m³. As with all chemicals, exposure should be kept to the lowest possible levels. TWA (Time Weighted Average): The average airborne concentration of a particular substance when calculated over a normal eight-hour working day, for a five-day week. Source: Safe Work Australia

9. PHYSICAL AND CHEMICAL PROPERTIES

Form

Solid

Appearance

White granular powder with a slight chlorine odour.

Colour

White

Odour

Slight smell of chlorine.

Decomposition Temperature

Not available

Melting Point

Not available

Boiling Point

Not available

Solubility in Water

Soluble in water with generation of heat.

Specific Gravity

Not available

pH

Very alkaline. 12.3-12.6 (1% solution)

Vapour Pressure

Not available

Vapour Density (Air=1)

Not available

Evaporation Rate

Not available

Odour Threshold

Not available

Viscosity

Refer to Section 9: Kinematic Viscosity and Dynamic Viscosity

Partition Coefficient: n-octanol/water

Not available

Flash Point

Not available

Flammability

Not combustible. Contact with aluminium, tin, zinc or galvanised iron may generate hydrogen, a flammable gas.

Auto-Ignition Temperature

Not available

Explosion Limit - Upper

Not available

Explosion Limit - Lower

Not available

Explosion Properties

Not available

Oxidising Properties

Not available

Kinematic Viscosity

Not available

Dynamic Viscosity

Not available

10. STABILITY AND REACTIVITY

Reactivity

Refer to Section 10: Possibility of hazardous reactions.

Chemical Stability

Stable under normal conditions of storage and handling.

Conditions to Avoid

Extremes of temperature and direct sunlight

Incompatible materials

Not available.

Hazardous Decomposition Products

Will react vigorously or violently with acids, generating great heat and carbon dioxide, a simple asphyxiant and chlorine, a toxic gas. Contact with moisture will generate chlorine. May react violently with calcium hypochlorite. Contact with aluminium, tin, zinc or galvanised iron will generate hydrogen, a flammable gas. Contact with ammonium compounds will generate ammonia, a poisonous gas.

Possibility of hazardous reactions

Not available.

Hazardous Polymerization

Not available.

11. TOXICOLOGICAL INFORMATION

Toxicology Information

No toxicity data available for this material.

Ingestion

Ingestion of this product will cause nausea, vomiting, abdominal pain and chemical burns to the mouth, throat and stomach.

Inhalation

Dust generated will cause irritation with possible burns to the mucous membrane and upper airways. Symptoms may include coughing, lesions of the nasal septum, severe pain and may lead to permanent tissue scarring. May cause respiratory irritation. Inhalation of product dust can cause irritation of the nose, throat and respiratory system.

Skin

Causes burns. Corrosive to the skin. Skin contact can cause redness, itching, irritation, severe pain and chemical burns with resultant tissue destruction.

Eye

Causes eye damage. Eye contact will cause stinging, blurring, tearing, severe pain and possible burns, necrosis, permanent damage and blindness.

Respiratory sensitisation

Not expected to be a respiratory sensitiser.

Skin Sensitisation

Not expected to be a skin sensitiser.

Germ cell mutagenicity

Not considered to be a mutagenic hazard.

Carcinogenicity

Not considered to be a carcinogenic hazard.

Reproductive Toxicity

Not considered to be toxic to reproduction.

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure

Not expected to cause toxicity to a specific target organ.

Aspiration Hazard

Not expected to be an aspiration hazard.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects.

Persistence and degradability

Not available

Mobility

Not available

Bioaccumulative Potential

Not available

Other Adverse Effects

Not available

Environmental Protection

Prevent large amounts from entering waterways, drains and sewers.

13. DISPOSAL CONSIDERATIONS

Disposal considerations

Dispose of waste according to applicable local and national regulations. Do not allow into drains or watercourses or dispose of where ground or surface waters may be affected. Wastes including emptied containers are controlled wastes and should be disposed of in accordance with all applicable local and national regulations.

14. TRANSPORT INFORMATION

Transport Information

This material is classified as a Class 8 Corrosive Substances Dangerous Goods

Class 8 Dangerous Goods are incompatible in a placard load with any of the following:

- Class 1: Explosives
 - Division 4.3: Dangerous when wet Substances
 - Division 5.1: Oxidising substances
 - Division 5.2: Organic peroxides
 - Class 6, Toxic or Infectious Substances, if the Class 6 dangerous goods are cyanides and the Class 8 dangerous goods are acids
 - Class 7: Radioactive materials unless specifically exempted
- and are incompatible with food and food packaging in any quantity.

Strong acids must not be loaded in the same freight container or on the same vehicle with strong alkalis. Packing Group I and II acids and alkalis should be considered as strong.

Marine Transport (IMO/IMDG):

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

Class/Division: 8

UN No: 1759

Proper Shipping Name: CORROSIVE SOLID, N.O.S. (CONTAINS: SODIUM HYDROXIDE) (MARINE POLLUTANT)

Packing Group: II
EMS : F-A, S-B
Special Provision: 274

Air Transport (ICAO/IATA):
Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

Class/Division: 8
UN No: 1759
Proper Shipping Name: corrosive solid, n.o.s. (Contains: sodium hydroxide)
Packing Group: II
Packaging Instructions (passenger & cargo): 859
Packaging Instructions (cargo only): 863
Hazard Label: Corrosive
Special Provision: A3, A803

U.N. Number

1759

UN proper shipping name

CORROSIVE SOLID, N.O.S.(Contains: Sodium hydroxide)

Transport hazard class(es)

8

Packing Group

II

Hazchem Code

2X

Special Precautions for User

Not available

IERG Number

37

IMDG Marine pollutant

Yes

Transport in Bulk

Not available

15. REGULATORY INFORMATION

Regulatory information

Classified as Hazardous according to the Globally Harmonised System of classification and labelling of chemicals (GHS) including Work, Health and Safety regulations, Australia

Classified as a Scheduled Poison according to the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP)

Poisons Schedule

S6

16. OTHER INFORMATION

Date of preparation or last revision of SDS

SDS created: May 2016

References

Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice.

Standard for the Uniform Scheduling of Medicines and Poisons.

Australian Code for the Transport of Dangerous Goods by Road & Rail.

Model Work Health and Safety Regulations, Schedule 10: Prohibited carcinogens, restricted carcinogens and restricted hazardous chemicals.

Workplace exposure standards for airborne contaminants.

Adopted biological exposure determinants, American Conference of Industrial Hygienists (ACGIH).
Globally Harmonised System of classification and labelling of chemicals.

Contact Person/Point

The company has taken care in compiling this information. No liability is accepted whether direct or indirect from its application since the conditions of final use are outside the Company's control. The end user is obliged to conform to relevant government regulations and/or patent laws applicable in their respective States of Countries.

24-Hour Emergency Telephone: AUS: 1800 629 953 NZ: Poisons 0800 764 766,

END OF SDS

© Copyright Chemical Safety International Pty Ltd

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe SDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe SDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

The compilation of SDS's displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copying of any SDS displayed is permitted for personal use only and otherwise is not permitted. In particular the SDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of SDS without the express written consent of Chemical Safety International Pty Ltd.